

Version 16.1 replaces Version 15.1 Revision date: 01.04.2016 According to (EU) No. 2015/830

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier: MAGNAGLO® 410HF - aerosol

1.2 Relevant identified uses of the mixture and uses advised against:

Relevant identified uses: Fluorescent magnetic ink used in Magnetic

Particle Inspection (MPI).

Uses advised against: This product is not recommended for any

use other than the identified uses above.

1.3 Details of the supplier of the safety data sheet

Manufacturer: Magnaflux® (A Division of ITW Ltd)
Address: Faraday Road, South Dorcan Industrial

Estate, Swindon, UK

Postcode: SN3 5HE

Telephone/fax number: Telephone: +44 (0)1793 524566

Fax: +44 (0)1793 490459 Web: www.eu.magnaflux.com

Email address of competent person datasheets@magnaflux.co.uk

responsible for SDS:

National contact: None appointed.

1.4 Emergency telephone number: T: +44 (0)1793 524566 (office hours)

Opening hours: Office hours (GMT) Monday - Thursday 8am

- 5pm, Friday 8am - 4pm

Other comments: Emergency telephone service is provided in

English only.

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

Classification according to Regulation Physical and Chemical Hazard:

(EC) No 1272/2008 (CLP): Aerosol 1 H222, H229

Health Hazard:

None

Environmental Hazard:

None

Additional information EUH066.

For full text of hazard statements and EU hazard statements see SECTION 16.

2.2 Label Elements:

Labelling according to regulation (EC) No 1272/2008 [CLP]

Hazard Pictograms:

Signal Word: Danger

Hazard Statement(s): H222: Extremely flammable aerosol. H229: Pressurised container. May burst if

heated.

Precautionary Statement(s): P210: Keep away from heat, hot surfaces,

sparks, open flames or other ignition

sources. No smoking.

P211: Do not spray on an open flame or

other ignition source.

P251: Do not pierce or burn even after use. P280: Wear protective gloves/protective clothing/eye protection/face protection. P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501: Dispose of contents/container to hazardous waste or special collection point.

Supplementary Precautionary

Statement(s):

Supplementary Hazard Information

(EU)

Hazard Determining Component(s)

EUH066: Repeated exposure may cause

skin dryness and cracking.

Not applicable.

None.

2.3 Other hazards:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Vapours can form explosive mixtures with air.

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

Ingredient Name	CAS No	EC No	REACH Registration Number	% Weight	Classification according to Regulation (EC) No 1272/2008 [CLP]	Additional information
Hydrocarbons C12-C15 n- alkanes, isoalkanes, cyclic, < 2% aromatics		920- 107-4	01- 2119453414- 43	> 65	Asp. Tox. 1: H304 (note 1)	EUH066
Hydrocarbons, C3-4-rich petroleum distillate petroleum gas (1.3 butadiene < 0.1%)	68512- 91-4	270- 990-9	(note2)	10-30	Press. Gas H280, Flam. Gas 1 H220	(note3)

Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished products.

^{2.} Exempted from the obligation to register in accordance with art.2(7)(a) of REACH Regulation No 1907/2006

^{3.} Not classified as carcinogen, less than 0.1% w/w 1,3 butadiene (EINECS no 203-450-8)

^{*}See Section 16 for hazard statement(s) text in full.

SECTION 4 FIRST AID MEASURES

4.1 Description of first aid measures:

Following skin contact:

General notes: If symptoms persist, seek medical attention.

Show this safety data sheet to the doctor in

attendance.

Following inhalation: Remove to fresh air. Keep at rest. If not

breathing give artificial respiration. Seek medical attention if symptoms occur. Flush with water, use soap if available.

Contaminated clothing should be washed

before re-use.

Following eye contact: Flush eyes with large amounts of water for

at least 10 minutes. Seek medical attention

if irritation persists.

Following ingestion: Unlikely route of exposure. Do NOT induce

vomiting. If vomiting occurs, keep head low so that stomach contents don't enter the lungs. Never give anything by mouth to an

unconscious person. Seek medical attention immediately.

Self-protection of the first aider:No action shall be taken involving any

personal risk or without suitable training. If it is suspected that the mixture is still present,

wear appropriate personal protective

equipment.

4.2 Most important symptoms, both acute and delayed:

May cause lung damage if swallowed. No delayed effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

None known.

SECTION 5 FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media: Carbon dioxide, foam, dry chemical, water

fog or spray.

Unsuitable extinguishing media:

Do not use water jet.

5.2 Special hazards arising from the substance or mixture:

Evacuate immediate area. Shut off 'fuel' to

fire. If possible keep unaffected containers

cool with water spray.

Aerosols may explode in a fire.

Aerosol contents are extremely flammable.

Hazardous combustion products: Smoke, soot and oxides of carbon. Burning

vapour may give off toxic fumes.

5.3 Advice for fire-fighter:

Warn firefighters that aerosols are involved.

Self contained breathing apparatus and full protective clothing must be worn.

Water spray should be used to cool containers.

Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Suitable protective equipment (see Section 8) should be worn to prevent any

contamination of skin, eyes and personal clothing.

For non-emergency personnel: Shut off ignition sources.

Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Vapours are

likely to accumulate in low areas.

For emergency responders: Keep unnecessary people at a safe

distance.

Shut off ignition sources.

Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Vapours are

likely to accumulate in low areas.

6.2 Environmental precautions:

Prevent liquid from entering drains, sewers and watercourses. Notify the Environment Agency or water authorities if a major spillage occurs.

6.3 Methods and material for containment and cleaning up:

Eliminate sources of ignition. Take measures to prevent the build-up of electrostatic charge.

For containment: Contain spillage, and then collect with non-

combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite). Place in a container for disposal according

to local/national regulations.

Large spills should be pumped into containers pending disposal. Dispose of

waste according to local/national

regulations.

For cleaning up: Allow residues to evaporate. Do not flush

away residues with water.

Other information: No other information.

6.4 Reference to other sections:

For Personal Protective Equipment see Section 8. For disposal information see Section 13.

SECTION 7 HANDLING & STORAGE

7.1 Precautions for safer handling:

Protective Measures: Wear suitable protective clothing such as

chemical resistant gloves, apron and goggles/face mask to protect from splashes. Ensure adequate exhaust ventilation when

in use.

Avoid contact with skin and eyes.

Do not breathe product spray or mist.

Measures to prevent fire: Aerosol contents are highly flammable and

volatile. Keep away from sources of ignition – no smoking. Take measures to prevent the build-up of electrostatic charge. Equipment should be earthed. Use

explosion proof electrical/ventilation/lighting equipment. Use only non-sparking tools.

Advice on general occupational Wash thoroughly after handling.

hygiene:

7.2 Conditions for safe storage, including any incompatibilities:

Technical measures and storageStore in a cool dry area away from heat and

conditions: sources of ignition.

Keep containers tightly closed when not in

use.

Packaging materials: Store in original container.

Requirements for storage rooms and

vessels:

Pressurised container: protect from sunlight

and do not expose to temperatures

exceeding 50 °C.

Recommended storage temperature 10 °C

to 30 °C.

Further information on storage

conditions:

Rotate stock and check regularly for

damaged items.

7.3 Specific end use(s):

Recommendations: Use only for Non Destructive Testing (NDT)

applications.

Industrial sector specific solutions: See product data sheet for further

information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

Occupational exposure limit values:

Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

Ingredient name	Country	Limit valu	Limit value - 8 hours		Limit value - short term	
		ppm	mg/m³	ppm	mg /m³	
Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics	Supplier's recommendation	150	1200			
Data obtained from supplier's SDS						

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) – Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	No threshold effect and/or no dose- response information available.
Worker	Inhalation	Short term	Local	No threshold effect and/or no dose- response information available.
Worker	Dermal	Long term	Systemic	No threshold effect and/or no dose- response information available.

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygenists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Predicted No Effect Concentration (PNEC) - Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

Water - Fresh Water	No data available, testing technically not feasible.
Water - Marine Water	No data available, testing technically not feasible.
Water - Intermittent release	No data available, testing technically not feasible.
Sediment - Fresh water	No data available, testing technically not feasible.
Sediment - Marine water	No data available, testing technically not feasible.
Soil	No data available, testing technically not feasible.
Sewage Treatment plant	No data available, testing technically not feasible.

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable. Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

Appropriate engineering controls:

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure

limits are not exceeded.

Personal protection equipment:

Skin protection - other:

Eye and face protection: Safety glasses with side-shields

conforming to EN166.

Skin protection - hand: Protective gloves conforming to EN374.

Use chemical resistant gloves

recommended by glove manufacturer as being suitable for **kerosenes** if hand

exposure is unavoidable.

Protective gloves made of nitrile,

neoprene or PVC are suitable, although other types may be more suitable in other

circumstances.

For prolonged exposure, recommended gloves with protective index 6, > 480 minutes permeation time according to

EN374.

As the product is a preparation, consult

the glove manufacturer for exact

breakthrough time. Glove manufacturer's directions for use should be observed. Wear impervious, flame retardant

antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the

specific workplace.

Respiratory protection: If ventilation is insufficient, suitable

respiratory protection must be provided. Chemical respirator with organic vapour cartridge. Use respiratory equipment with

gas filter, type A2. EN 136/140/145/143/149.

For higher level protection use type ABEK-P3 (EU EN 143) respirator cartridges. Use respirators and

components tested and approved under

CEN standards.

Thermal hazards: Not applicable.

Environmental exposure controls: Avoid any release to the environment.

SECTION 9 PHYSICAL & CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance: Aerosol containing mobile dark green liquid.

Odour: Mild hydrocarbon.
Odour threshold: No data available.

pH: Neutral.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: 230 °C

Flash point (PMCC): -40 °C (aerosol propellant)

Evaporation rate (BuAC = 100): < 0.1

Flammability (solid, gas) (Limits in air): No data available. Upper/lower flammability or explosive 1.0 - 6.0 % (Vol%)

limits:

Vapour pressure: < 0.5 mm Hg @ 20 °C

Vapour density (Air = 1): > 1

Relative density: 0.80 g/cm³ **Solubility:** Negligible.

Partition coefficient: n-octanol/water: No data available.

Auto-ignition temperature: > 200 °C

Decomposition temperature:No data available.Viscosity (ASTM D445):2.5 mm²/s @ 38 °CExplosive properties:No data available.Oxidising properties:No data available.

Note: properties relate to the bulk product only unless otherwise stated.

9.2 Other information:

Reactivity:

10.1

No other information.

SECTION 10	STABILITY & REACTIVITY

	•	
10.2	Chemical stability	Stable under normal conditions of use and applications.
10.3	Possibility of hazardous reactions:	No data available.
10.4	Conditions to avoid:	Keep away from sources of ignition, hot surfaces and direct sun light.
10.5	Incompatible materials:	Strong oxidising agents. Acids and alkalis.

10.6 Hazardous decomposition materials: None under normal conditions of use.

Smoke, soot and oxides of carbon on

combustion.

No data available.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: based on data for component materials.

Acute toxicity - oral:Based on the available data, the classification

criteria are not met.

Acute toxicity – dermal: Based on the available data, the classification

criteria are not met.

Acute toxicity – inhalation: Based on the available data, the classification

criteria are not met.

Skin corrosion/irritation: EUH066: Repeated exposure may cause skin

cracking or dryness.

Serious eye damage/irritation: Based on the available data, the classification

criteria are not met.

Respiratory sensitisation: Non sensitizing. Based on the available data

the classification criteria are not met.

Skin sensitisation: Non sensitizing. Based on the available data

the classification criteria are not met.

Germ cell mutagenicity:Based on the available data, the classification

criteria are not met.

Carcinogencity: Based on the available data, the classification

criteria are not met.

Reproductive toxicity: Based on the available data, the classification

criteria are not met.

STOT single exposure: Based on the available data, the classification

criteria are not met.

STOT repeated exposure: Based on the available data, the classification

criteria are not met.

Aspiration hazard: Mixtures from Aerosol Dispensors - need not

be classified as Asp. Tox. 1 - H304 as the aerosol spray is fine and a pool of product

may not be formed in the mouth.

Information on likely Routes of Exposure and Potential Health Effects:

Inhalation: May cause irritation to the respiratory system.

Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and

intoxication.

Ingestion: Not a likely route of entry, however, may be

fatal if swallowed and enters airways. Small amounts of product aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary edema. Ingestion may cause irritation of the mouth, throat and digestive

tract.

Eye contact: May cause irritation.

Skin contact: May be harmful if absorbed through skin.

May cause skin irritation.

EUH066: Repeated exposure may cause skin

cracking or dryness.

Toxicity Test Results: based on data for component materials, where available.

Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

Acute Toxicity – oral	LD50 (rat)	> 5000 mg/kg (OECD 401)
Acute Toxicity – dermal	LD50 (rabbit)	> 5000 mg/kg (OECD 402)
Acute Toxicity – inhalation	LC50 (rat)	4951 mg/l (vapours) 4h (OECD403)

Other Information: No other information.

SECTION 12 ECOLOGICAL INFORMATION

Based on data for component materials

12.1 Toxicity:

Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

Fish	Onchorhynchus mykiss	LC0	96h	1000 mg/l
Aquatic Invertebrates				No data available.
Aquatic Plants				No data available
Microorganisms				No data available

12.2 Persistence and degradability: Expected to be biodegradable.

12.3 Bioaccumulative potential: No data available.

Partition coefficient: n-octanol/water

(log Kow):

No data available.

Bioconcentration factor (BCF): No data available.

12.4 Mobility in soil: This product is insoluble in water.

12.5 Results of PBT and vPvB assessment: This mixture does not contain any

substances that are assessed to be a PBT or

vPvB.

12.6 Other adverse effects: No data available.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation.

Product/packing disposal: Empty containers may contain residual

product and flammable vapours. Do not pierce or burn container even after use. Do NOT remove labels. Keep away from

sources of ignition.

Waste codes/waste designations 16 05 04* gases in pressure containers

according to LoW: containing dangerous substances.

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

Waste treatment – relevant information: Dispose of waste and residues in

accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in

disposal at a licensed facility in accordance with national legislation Do not empty down the drain.

Sewage disposal – relevant

information:

Other disposal recommendations: Use a licensed waste contractor.

SECTION 14 TRANSPORT INFORMATION

14.1 **UN number:** ADR/RID: 1950 IMDG: 1950 IATA: 1950 14.2 AEROSOLS, flammable. **UN proper shipping name:** ADR/RID: IMDG: AEROSOLS, flammable AEROSOLS, flammable IATA: 14.3 Transport hazard class(es): ADR/RID: 2.1 IMDG: 2.1 IATA: 2.1 14.4 Packing group: ADR/RID: N/A N/A IMDG: IATA: N/A 14.5 **Environmental hazards:** ADR/RID: No IMDG: No IATA: No

14.6 Special precautions for user:

ADR/RID – Tunnel code: (D) IMDG - Ems: F-D, S-U IATA/ICAO - PAX: 203 IATA/ICAO - CAO: 203

14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC code:

Not applicable.

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations:

This data sheet complies with the requirements of Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures.

Safety data sheet as required by EC-Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.

Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.

This data sheet is complied according Dir 2013/10/EU, 2008/47/EEC amendment of the aerosol directive 75/324/EEC.

Extra label elements: Pressured container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

National regulations (Germany):

Wassergefahrdungklasse (water WGK 1 – Low hazard to waters.

hazard class):

TechnischeAnleitungLuft (TA-Luft): Class 5.2.5 Organic Substances, except

dusts

15.2 **Chemical safety assessment:**

No chemical safety assessment has been carried out for this mixture by the supplier.

SECTION 16 OTHER INFORMATION

(i) Indication of changes:

This safety data sheet has been updated to meet the requirements of Regulation EU No 2015/830 and Regulation (EC) No 1272/2008. Removal of the classification according to 67/548/EEC as amended & Directive 1999/45/EC. Version 16.1 also updated in Section 8 due to updated safety information.

Vertical lines on the left hand side indicate an amendment from the previous version.

(ii) Abbreviations and acronyms:

ADR European Agreement concerning the International Carriage of Dangerous Goods

by Road (Accord européen relatif au transport international des marchandises

Dangereuses par Route)

CAS No. Chemical Abstracts Service number
CEN European Committee for Standardisation

CLP Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008

ECHA European Chemicals Agency

EC50 Half Maximal Effective Concentration

EC number EINECS and ELINCS number

EINECS European Inventory of Existing Commercial Substances

ELINCS European List of notified Chemical Substances

GHS Globally Harmonized System

IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC50 Lethal Concentration to 50% of a test population

LD50 Lethal Dose to 50% of a test population

MPI Magnetic Particle Inspection
NDT Non-Destructive Testing
OEL Occupational Exposure Limit

PBT Persistent, Bioaccumulative and Toxic Substance

PMCC Pensky-Martens closed cup method PPE Personal Protection Equipment

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

EC (No) 1907/2006

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

(Reglement International concernant le transport des marchandises Dangereuses

par chemin de fer)

SDS Safety Data Sheet

STOT RE Specific Target Organ Toxicity, Repeat Exposure STOT SE Specific Target Organ Toxicity, Single Exposure

TA-Luft Technical Instructions on Air Quality Control (Technische Anleitung zur

Reinhaltung der Luft)

vPvB Very Persistent and Very Bioaccumulative

WEL Workplace Exposure Limit

WGK German Water Hazard Class (Wassergefährdungsklasse)

(iii) Key literature and sources of data:

- Supplier's safety data sheets for components listed in Section 3.
- European Chemicals Agency, http://echa.europa.eu/
- GESTIS International Limit Values Database, http://limitvalue.ifa.dguv.de/Webform_gw.aspx
- Occupational Exposure Limits EH40/2005.
- Commission regulation (EU) 2015/830.
- Control of Substances Hazardous to Health Regulations 2002.
- Hazardous waste regulations 2005.
- Health & Safety at Work Act 1974.
- REACH Directive (EC) 1907/2006.

(iv) Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):

Classification according to Regulation (EC) No 1272/2008	Classification procedure	
Aerosol 1 H222	Test	
Aerosol 1 H229	Test	
EUH066	Calculation	

(v) Hazard statements (number and full text):

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H229: Pressurised container: may burst if heated.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

EUH066: Repeated exposure may cause skin dryness or cracking

Hazard Class and Category Code (full text):

Aerosol 1: Aerosol

Asp. Tox. 1: Aspiration Hazard Flam. Gas 1: Flammable Gas Press. Gas: Gases under pressure

Relevant precautionary statements (number and full text):

P210: Keep away from heat, hot surfaces, sparks, open flames or other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501: Dispose of contents/container to hazardous waste or special collection point.

(vi) Training advice:

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment. Provide adequate information, instruction and training to operators.

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-to-date and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

Revision Revision This SDS is valid from the Revision Date. If you require a SDS for the summary: Comments product manufactured before the revision date please contact us at

datasheets@magnaflux.co.uk.

Revision Date 01.04.2016

Version 16.1