

Version 17.1 replaces Version 16.1 Revision date: 01.01.2017 According to (EU) No. 2015/830

| SECTION 1 IDENTIFICATION OF T COMPANY / UNDERT | | | / MIXTURE AND OF THE |
|---------------------------------------------------|-------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------|
| 1.1 | Product identifier: | SPOTCHEC | K® SKC-S - aerosol |
| 1.2 | Relevant identified uses of the mixture Relevant identified uses: | | d against: ner used in penetrant |
| | Uses advised against: | This product | is not recommended for any n the identified uses above. |
| 1.3 | Details of the supplier of the safety data Manufacturer: Address: | Magnaflux® (| (A Division of ITW Ltd) d, South Dorcan Industrial |
| | Postcode: Telephone/fax number: | SN3 5HE Telephone: Fax: Web: | |
| | Email address of competent person responsible for SDS: | datasheets@ | magnaflux.co.uk |
| | National contact: | None appoint | ted. |
| 1.4 | Emergency telephone number: | T: +44 (0)179 | FICE HOURS, CALL 93 524566 (English only) |
| | Opening hours: | - 5pm, Friday | FICE HOURS, CALL |

SECTION 2

HAZARDS IDENTIFICATION

| 2.1 | Classification of the substance or mixture: | | | | |
|-----|---------------------------------------------|-------------------------------|--|--|--|
| | Classification according to Regulation | Physical and Chemical Hazard: | | | |
| | (EC) No 1272/2008 (CLP): | Aerosol 1 H222, H229 | | | |
| | | Health Hazard: | | | |
| | | Skin Irrit. 2 H315 | | | |
| | | STOT SE 3 H336 | | | |
| | | Environmental Hazard: | | | |

Additional information

For full text of hazard statements and EU hazard statements see SECTION 16.

Aquatic Chronic 2 H411

No other information.

2.2

Label Elements:

Labelling according to regulation (EC) No 1272/2008 [CLP]

| Signal Word: Hazard Statement(s): | DANGER H222: Extremely flammable aerosol. |
|-----------------------------------------|---------------------------------------------------------------------------------------|
| | H229: Pressurised container: may burst if heated. |
| | H315: Causes skin irritation H336: May cause drowsiness or dizziness |
| | H411: Toxic to aquatic life with long lasting effects |
| Precautionary Statement(s): | P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition |
| | sources. No smoking. |
| | P211: Do not spray on an open flame or other ignition source. |
| | P251 Do not pierce of burn even after use. |
| | P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. |
| | P261: Avoid breathing dust/fume/gas/mist/vapours/spray. |
| | P280: Wear protective gloves/protective |
| | clothing/eye protection/face protection. P501: Dispose of contents/container to |
| Supplementary Precautionary | hazardous waste or special collection point. P271: Use only outdoors or in a well |
| Statement(s): | ventilated area. |
| | P302+352: IF ON SKIN: Wash with soap and water |
| | P264: Wash thoroughly after handling. |
| | P362+P364: Take off contaminated clothing and wash it before reuse. |
| Supplementary Hazard Information | None |
| (EU) Hazard Determining Component(s) | Hydrocarbons, C7 – C9, isoalkanes |

2.3 Other hazards:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Vapours can form explosive mixtures with air.

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

| Ingredient Name | CAS No | EC No | REACH Registration Number | % Weight | Classification according to Regulation (EC) No 1272/2008 [CLP] | Additional information |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-------|---------------------------------|-------------|----------------------------------------------------------------------|------------------------|
| Hydrocarbons, C7- C9, | | 921- | 01- | 60 -100 | Flam. Liq 2: H225 | No other |
| isoalkanes | | 728-3 | 2119471305- | | Skin Irrit. 2: H315 | information |
| | | | 42 | | STOT SE3: H336 | |
| | | | | | Asp. Tox. 1: H304 (note1) | |
| | | | | | Aquatic Chronic 2: H411 | |
| Hydrocarbons, C3-4-rich | 68512- | 270- | (note2) | 10-30 | Press. Gas H280 | (note3) |
| petroleum distillate petroleum | 91-4 | 990-9 | | | Flam. Gas 1 H220 | |
| gas (1.3 butadiene < 0.1%) | | | | | | |
| 1. Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a scaled spray attachment | | | | | | |

containers fitted with a sealed spray attachment.
Exempted from the obligation to register in accordance with art.2(7)(a) of REACH Regulation No 1907/2006

Not classified as carcinogen, less than 0.1% w/w 1,3 butadiene (EINECS no 203-450-8)

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished products.

*See Section 16 for hazard statement(s) text in full.

| SECTIO | N 4 FIRST AID MEASURES | |
|--------|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4.1 | Description of first aid measures: General notes: | If symptoms persist, seek medical attention. Show this safety data sheet to the doctor in |
| | Following inhalation: | attendance. Remove to fresh air. Keep at rest. If not breathing give artificial respiration. Seek prompt medical attention if discomfort persists. |
| | Following skin contact: | Flush with water, use soap if available. Contaminated clothing should be washed before re-use. Seek medical attention if irritation persists. |
| | Following eye contact: | Flush eyes with large amounts of water for at least 15 minutes with eyelids held open. Seek medical attention if irritation persists. |
| | Following ingestion: | Unlikely route of exposure. Rinse mouth with water. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach contents don't enter the lungs. Never give anything by mouth to an unconscious person. Seek medical attention immediately. |
| | Self-protection of the first aider: | No action shall be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate personal protective equipment. |

4.2 Most important symptoms, both acute and delayed:

Prolonged skin contact may cause redness and irritation. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects. Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation. Avoid vomiting and normal rinse of stomach because of risk of aspiration. May cause discomfort to the eyes. Symptoms: redness and pain.

4.3 Indication of any immediate medical attention and special treatment needed: None known.

| SECTION | I 5 FIREFIGHTING MEASUR | RES |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5.1 | Extinguishing media: Suitable extinguishing media: | Carbon dioxide, foam, dry chemical, water |
| 5.2 | Unsuitable extinguishing media: Special hazards arising from the substance or mixture: | fog or spray. Do not use water jet. Evacuate immediate area. Shut off 'fuel' to fire. If possible keep unaffected containers cool with water spray. Aerosols may explode in a fire. Aerosol contents are extremely flammable. |
| | Hazardous combustion products: | Smoke, soot and oxides of carbon. Burning vapour may give off toxic fumes. |
| 5.3 | Advice for fire-fighter: Warn firefighters that aerosols are involved. protective clothing must be worn. Water sp Contaminated extinguishing water must be regulations. | Self contained breathing apparatus and full ray should be used to cool containers. |
| SECTION | 6 ACCIDENTAL RELEASE | MEASURES |
| 6.1 | Personal precautions, protective equipm Suitable protective equipment (see Section contamination of skin, eyes and personal clo For non-emergency personnel: For emergency responders: | 8) should be worn to prevent any |
| 6.2 | Environmental precautions: Prevent liquid from entering drains, sewers Agency or water authorities if a major spillag | and watercourses. Notify the Environment |
| 6.3 | Methods and material for containment ar Eliminate sources of ignition. Take measure charge. Avoid breathing vapours. Ventilate surround For containment: | s to prevent the build-up of electrostatic |
| 6.4 | Reference to other sections: For Personal Protective Equipment see Sec 13. | tion 8. For disposal information see Section |

| Precautions for safer handling: | |
|---------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective Measures: | Wear suitable protective clothing such as chemical resistant gloves, apron and goggles/face mask to protect from splashes. Ensure adequate exhaust ventilation when in use. |
| Measures to prevent fire: Advice on general occupational hygiene: | Avoid contact with skin and eyes. Do not breathe product spray or mist. Risk of vapour concentration in low areas. Aerosol contents are highly flammable and volatile. Keep away from sources of ignition – no smoking. Take measures to prevent the build-up of electrostatic charge. Equipment should be earthed. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Wash thoroughly after handling. |
| Conditions for safe storage, including any Technical measures and storage conditions: Packaging materials: | incompatibilities: Store in a cool dry area away from heat and sources of ignition. Store in original container. |
| Requirements for storage rooms and vessels: | Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Recommended storage temperature 10 °C to 30 °C. |
| Further information on storage conditions: Specific end use(s): | Rotate stock and check regularly for damaged items. |
| Recommendations: | Use only for Non Destructive Testing (NDT) applications. See product data sheet for further |
| | Advice on general occupational hygiene: Conditions for safe storage, including any Technical measures and storage conditions: Packaging materials: Requirements for storage rooms and vessels: Further information on storage conditions: Specific end use(s): |

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

Occupational exposure limit values:

Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

| | | Limit value - 8 hours | | Limit value - short terr | |
|----------------------------------------------------------------------------|---------|-----------------------|--------------------|--------------------------|--------------------|
| Ingredient name | Country | ppm | mg /m ³ | ppm | mg /m ³ |
| Hydrocarbons, C7 – C9, isoalkanes | UK | 241 | 1200 | | |
| Data abtained from CESTIS International Limit Values, EH40, auguliar's SDS | | | | | |

Data obtained from GESTIS International Limit Values, EH40, supplier's SDS

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) - Hydrocarbons, C7 - C9, isoalkanes

| End User | Exposure Route | Exposure Time | Effects | DNEL |
|----------|----------------|---------------|----------|------------------------|
| Worker | Inhalation | Long term | Systemic | 2035 mg/m ³ |
| Worker | Dermal | Long term | Systemic | 773 mg/kg bw/day |

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygenists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Predicted No Effect Concentration (PNEC) - Hydrocarbons, C7 - C9, isoalkanes

| Water - Fresh Water | No data available: testing technically not feasible |
|------------------------------|-----------------------------------------------------|
| Water - Marine Water | No data available: testing technically not feasible |
| Water - Intermittent release | No data available: testing technically not feasible |
| Sediment - Fresh water | No data available: testing technically not feasible |
| Sediment - Marine water | No data available: testing technically not feasible |
| Soil | No data available: testing technically not feasible |
| Sewage Treatment plant | No data available: testing technically not feasible |
| | |

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable. Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

| Appropriate engineering controls: | Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal protection equipment: | |
| Eye and face protection: | Safety glasses with side-shields conforming to EN166. |
| Skin protection - hand: | Protective gloves conforming to EN374-3. Use chemical resistant gloves recommended by glove manufacturer as being suitable for isoparaffins, if hand exposure is unavoidable. Protective gloves made of nitrile rubber are suitable, although other types may be more suitable in other circumstances. For prolonged exposure, recommended gloves with protective index 6, > 480 minutes permeation time according to EN374. |
| | Consult the glove manufacturer for exact breakthrough time. Glove manufacturer's directions for use should be observed. |
| Skin protection – other: | Wear impervious, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the specific workplace. |

| | Respiratory protection: | In case of insufficient ventilation, wear suitable respiratory equipment. Filter type A. (EN 136, 140, 405, 149, 143) For higher level protection use type ABEK-P3 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under CEN standards. |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | Thermal hazards: | Not applicable. |
| | Environmental exposure controls: | Avoid any release to the environment. |
| SECTION | I 9 PHYSICAL & CHEMICAL P | ROPERTIES |
| 9.1 | Information on basic physical and chemical Appearance: Odour: Odour threshold: pH: Melting point/freezing point: Initial boiling point and boiling range: Flash point (PMCC): Evaporation rate (BuAc = 100): Flammability (solid, gas) (Limits in air): Upper/lower flammability or explosive limits: Vapour pressure: Vapour pressure: Vapour density (Air = 1): Relative density: Solubility: Partition coefficient: n-octanol/water: Auto-ignition temperature: Decomposition temperature: Viscosity (ASTM D445): Explosive properties: | A properties: Aerosol containing mobile clear liquid. Mild hydrocarbon. No data available. Neutral. No data available. 113 – 143 °C. -40 °C (aerosol propellant). 155. No data available. 0.7 - 6.0% (Vol%) 1.627 kPa @ 20 °C. > 1. 0.72 g/cm ³ . Insoluble. No data available. > 200 °C. No data available. 0.86 mm ² /s @ 25 °C. Under normal conditions no danger of explosion. No data available. |

Note: properties relate to the bulk product only unless otherwise stated.

9.2 Other information: No other information.

| SECTIO | ON 10 STABILITY & REACTIV | ТҮ |
|--------|-------------------------------------|-----------------------------------------------------------------------------------------|
| 10.1 | Reactivity: | No specific reactivity hazards associated with this product. |
| 10.2 | Chemical stability | Stable under normal conditions of use and applications. |
| 10.3 | Possibility of hazardous reactions: | No data available. |
| 10.4 | Conditions to avoid: | Keep away from sources of ignition, hot surfaces and direct sun light. |
| 10.5 | Incompatible materials: | Strong oxidising agents. |
| 10.6 | Hazardous decomposition materials: | None under normal conditions of use. Smoke, soot and oxides of carbon on combustion. |

1

| SECTION | N 11 TOXICOLOGICAL INFOR | RMATION | |
|----------------------------------------------|------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| 11.1 Information on toxicological effects: t | | ased on data for component materials. | |
| | Acute toxicity - oral: | Based on the available data, the classification criteria are not met. | |
| | Acute toxicity – dermal: | Based on the available data, the classification criteria are not met. | |
| | Acute toxicity – inhalation: | Based on the available data, the classification criteria are not met. | |
| | Skin corrosion/irritation: | Skin Irrit. 2 H315: Causes skin irritation. | |
| | Serious eye damage/irritation: | Based on the available data, the classification criteria are not met. | |
| | Respiratory sensitisation: | Data lacking. | |
| | Skin sensitisation: | Based on the available data, the classification criteria are not met. | |
| | Germ cell mutagenicity: | Based on the available data, the classification criteria are not met. | |
| | Carcinogencity: | Data lacking. | |
| | Reproductive toxicity: | Based on the available data, the classification criteria are not met. | |
| | STOT single exposure: STOT repeated exposure: Aspiration hazard: | STOT Single Exp. 3 H336: May cause drowsiness or dizziness. Affected organs: central nervous system Route of exposure: inhalation Based on the available data, the classification criteria are not met. Mixtures from Aerosol Dispensors - need not be classified as Asp. Tox. 1 - H304 as the | |
| | Information on likely Routes of Exposure | | |
| | Inhalation: Ingestion: | Vapour concentrations above the recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Not a likely route of exposure. However, harmful: May cause lung damage if swallowed. Ingestion may cause irritation of | |
| | Eye contact: Skin contact: | the mouth, throat and digestive tract. Small amounts of product aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary edema. May cause redness and pain. Frequent or prolonged contact with the product may produce irritation and/or skin dryness and cracking. Product will have a de- fatting effect on the skin. | |

Toxicity Test Results: based on data for component materials, where available.

| Hydrocarbons, C7 – C9, isoalkanes | | |
|-----------------------------------|---------------|-----------------------|
| Acute Toxicity – oral | LD50 (rat) | > 5000 mg/kg |
| Acute Toxicity – dermal | LD50 (rabbit) | > 2000 mg/kg |
| Acute Toxicity – inhalation | LC50 (rat) | 21 mg/l (4 h; vapour) |

Other Information:

No other information.

| SECTION 12 ECOLOGICAL INFORMATION |
|-----------------------------------|
|-----------------------------------|

Based on data for component materials

12.1 Toxicity:

Hydrocarbons, C7 – C9, isoalkanes

| Fish | Oncorhynchus mykiss | LL50 | 96h | 18.4 mg/l |
|-----------------------|---------------------------------|------|-----|-----------|
| Aquatic Invertebrates | Daphnia magna | EL50 | 48h | 2.4 mg/l |
| Aquatic Plants | Pseudokirchneriella subcapitata | EL50 | 72h | 29 mg/l |

| 12.3 Bioaccumulative potential: No data available. Partition coefficient: n-octanol/water (log Kow): Bioconcentration factor (BCF): No data available. 12.4 Mobility in soil: The product is immiscible with water and v spread on the water surface. Product is highly volatile - will partition rapidly to air. This mixture does not contain any | 12.2 | Persistence and degradability: | Hydrocarbons, C7 – C9, isoalkanes - Biodegradable. |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------------------------------------|-------------------------------------------------------|
| (log Kow): Bioconcentration factor (BCF): No data available. 12.4 Mobility in soil: The product is immiscible with water and v spread on the water surface. Product is highly volatile - will partition rapidly to air. This mixture does not contain any substances that are assessed to be a PBT | 12.3 | Bioaccumulative potential: | |
| 12.4 Mobility in soil: The product is immiscible with water and v spread on the water surface. Product is highly volatile - will partition rapidly to air. This mixture does not contain any substances that are assessed to be a PBT | | | No data available. |
| 12.5 Results of PBT and vPvB assessment: 12.5 Results of PBT and vPvB assessment: assessment: bight volatile - will partition rapidly to air. This mixture does not contain any substances that are assessed to be a PBT | | Bioconcentration factor (BCF): | No data available. |
| substances that are assessed to be a PBT | 12.4 | Mobility in soil: | • |
| | 12.5 | Results of PBT and vPvB assessment: | substances that are assessed to be a PBT or |
| 12.6 Other adverse effects: No data available. | 12.6 | Other adverse effects: | No data available. |

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation.

Product/packing disposal:
Empty containers may contain residual

| | product and flammable vapours. Do not pierce or burn container, even after use. Do NOT remove labels. Keep away from |
|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| | sources of ignition. |
| Waste codes/waste designations according to LoW: | 16 05 04* gases in pressure containers containing dangerous substances. |

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

| | Waste treatment – relevant information: Sewage disposal – relevant information: Other disposal recommendations: | accordance v requirements approved was disposal at a accordance v Do not empty | aste and residues in vith local authority . Seek the advice of an ste disposal contractor for licensed facility in vith national legislation v down the drain. |
|---------|--------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SECTION | I 14 TRANSPORT INFORMATI | ON | |
| 14.1 | UN number: | ADR/RID: IMDG: | UN1950 UN1950 |
| 14.2 | UN proper shipping name: | IATA: ADR/RID: | UN1950 AEROSOLS, flammable |

AEROSOLS, flammable IMDG: IATA: AEROSOLS, flammable 14.3 ADR/RID: Transport hazard class(es): 2.1 2.1 IMDG: 2.1 IATA: 14.4 ADR/RID: Packing group: N/A IMDG: N/A IATA: N/A 14.5 **Environmental hazards:** ADR/RID: Yes Marine Pollutant: Yes IMDG: IATA: Yes 14.6 Special precautions for user: ADD/DID Tunnol codo:

| The second state in the second state of the | |
|-------------------------------------------------|----------|
| IATA/ICAO – CAO: | 203 |
| IATA/ICAO – PAX: | 203 |
| IMDG – Ems: | F-D, S-U |
| ADR/RID – Tunnel code: | (D) |

14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC code: Not applicable

| SECTION 15 | | N 15 | REGULATORY INFORMATION | | |
|------------|------|------------------------------|----------------------------------------------------------------------------|--|--|
| | 15.1 | or mixture: EU Regulation | and environmental regulations/legislation specific for the substance s: | | |

This data sheet complies with the requirements of Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures.

Safety data sheet as required by EC-Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.

Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.

This data sheet is complied according Dir 2013/10/EU, 2008/47/EEC amendment of the aerosol directive 75/324/EEC.

Extra label elements: Pressured container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

National regulations (Germany): Wassergefahrdungklasse (water hazard class):

WGK 2 - Hazard to waters.

TechnischeAnleitungLuft (TA-Luft):

Class 5.2.5 Organic Substances, except dusts

15.2 Chemical safety assessment: No data available

| SEC | TION 16 | OTHER INFORMATION |
|-------|------------|--------------------------------------------------------------------------------------------------------|
| (i) | | of changes: |
| | | 1 updated in Section 1.4. |
| I | | s on the left hand side indicate an amendment from the previous version. |
| (ii) | | ons and acronyms: |
| | ADR | European Agreement concerning the International Carriage of Dangerous Goods |
| | | by Road (Accord européen relatif au transport international des marchandises Dangereuses par Route) |
| | CAS No. | Chemical Abstracts Service number |
| | CEN | European Committee for Standardisation |
| | CLP | Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008 |
| | ECHA | European Chemicals Agency |
| | EC50 | Half Maximal Effective Concentration |
| | EC number | |
| | EINECS | European Inventory of Existing Commercial Substances |
| | ELINCS | European List of notified Chemical Substances |
| | GHS | Globally Harmonized System |
| | IATA | International Air Transport Association |
| | IMDG | International Maritime Dangerous Goods |
| | LC50 | Lethal Concentration to 50% of a test population |
| | LD50 | Lethal Dose to 50% of a test population |
| | MPI NDT | Magnetic Particle Inspection |
| | OEL | Non-Destructive Testing Occupational Exposure Limit |
| | PBT | Persistent, Bioaccumulative and Toxic Substance |
| | PMCC | Pensky-Martens closed cup method |
| | PPE | Personal Protection Equipment |
| | REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation |
| | | EC (No) 1907/2006 |
| | RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| | | (Reglement International concernant le transport des marchandises Dangereuses |
| | | par chemin de fer) |
| | SDS | Safety Data Sheet |
| | STOT RE | Specific Target Organ Toxicity, Repeat Exposure |
| | STOT SE | Specific Target Organ Toxicity, Single Exposure |
| | TA-Luft | Technical Instructions on Air Quality Control (Technische Anleitung zur Reinhaltung der Luft) |
| | vPvB | Very Persistent and Very Bioaccumulative |
| | WEL | Workplace Exposure Limit |
| | WGK | German Water Hazard Class (Wassergefährdungsklasse) |
| (iii) | | erature and sources of data: |
| | • | Supplier's safety data sheets for components listed in Section 3. |
| | • | European Chemicals Agency, <u>http://echa.europa.eu/</u> |
| | • | GESTIS International Limit Values Database, |
| | | http://limitvalue.ifa.dguv.de/Webform_gw.aspx |
| | • | Occupational Exposure Limits EH40/2005. |
| | • | Commission regulation (EU) 2015/830. |
| | • | Control of Substances Hazardous to Health Regulations 2002. |
| | • | Hazardous waste regulations 2005. |
| | • | Health & Safety at Work Act 1974. |
| | • | Regulation (EC) No. 1907/2006 (REACH). |
| | • | Regulation (EC) No. 1272/2008 (CLP). |
| | | |

(iv) Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):

| Classification according to Regulation (EC) No 1272/2008 | Classification procedure |
|----------------------------------------------------------|--------------------------|
| Aerosol. 1: H222, H229 | Test Method |
| Skin Irrit. 2: H315 | Calculation Method |
| STOT SE3: H336: | Calculation Method |
| Aquatic Chronic 2: H411 | Calculation Method |

(v) Hazard statements (number and full text):

H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour

H222: Extremely flammable aerosol.

H229: Pressurised container: may explode if heated.

H280: Contains gas under pressure; may burst if heated.

H304: May be fatal if swallowed and enters airways

H315: Causes skin irritation

H336: May cause drowsiness or dizziness

H411: Toxic to aquatic life with long lasting effects

Hazard Class and Category Code (full text):

Aerosol 1: Aerosol

Aquatic Chronic 2: Hazardous to the aquatic environment

Asp. Tox. 1: Aspiration hazard

Flam. Gas 1: Flammable Gas

Flam. Liq. 2: Flammable liquid

Press. Gas: Gases under pressure

Skin Irrit. 2: Skin corrosion/irritation

STOT SE 3: Specific target organ toxicity - single exposure

Relevant precautionary statements (number and full text):

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251 Do not pierce of burn even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well ventilated area.

P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+352: IF ON SKIN: Wash with soap and water

P362+P364: Take off contaminated clothing and wash it before reuse.

P264: Wash thoroughly after handling.

P501: Dispose of contents/container to hazardous waste or special collection point.

(vi) Training advice:

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment. Provide adequate information, instruction and training to operators.

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-todate and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

| Revision summary: | Revision Comments | This SDS is valid from the Revision Date. If you require a SDS for the product manufactured before the Revision Date please contact us at datasheets@magnaflux.co.uk. |
|----------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | Revision Date Version | 01.01.2017 17.1 |