

Version 17.1 replaces Version 16.1 Revision date: 01.01.2017 According to (EU) No. 2015/830

SECTION 1

IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE **COMPANY / UNDERTAKING**

1.1 Product identifier: **ZYGLO® ZL-60C**

Relevant identified uses of the mixture and uses advised against: 1.2

> Relevant identified uses: Fluorescent penetrant used in Non

> > Destructive Testing (NDT) inspection.

This product is not recommended for any Uses advised against:

use other than the identified uses above.

Details of the supplier of the safety data sheet 1.3

Manufacturer: Magnaflux® (A Division of ITW Ltd)

Faraday Road, South Dorcan Industrial Address:

Estate, Swindon, UK

Postcode: SN3 5HE

Telephone/fax number: Telephone: +44 (0)1793 524566

> Fax: +44 (0)1793 490459

Web: www.eu.magnaflux.com **Email address of competent person** datasheets@magnaflux.co.uk

responsible for SDS:

National contact: None appointed.

1.4 **Emergency telephone number:** DURING OFFICE HOURS, CALL

T: +44 (0)1793 524566 (English only)

Office hours (GMT) Monday - Thursday 8am **Opening hours:**

- 5pm, Friday 8am - 4pm

OUT OF OFFICE HOURS, CALL

T: +44(0)203 394 9866

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

> Classification according to Regulation **Physical and Chemical Hazard:**

(EC) No 1272/2008 (CLP): None

Health Hazard:

Skin Irrit. 2 H315 Eye Dam. 1 H318 Asp. Tox. 1 H304 **Environmental Hazard:**

Aquatic Chronic 3 H412

Additional information EUH066

For full text of hazard statements and EU hazard statements see SECTION 16.

2.2 **Label Elements:**

Labelling according to regulation (EC) No 1272/2008 [CLP]

Hazard Pictograms:





Signal Word: Danger

Hazard Statement(s): H304: May be fatal if swallowed and enters

airways.

H315: Causes skin irritation.

H318: Causes serious eye damage. H412: Harmful to aquatic life with long

lasting effects.

P280: Wear protective gloves/protective **Precautionary Statement(s):**

> clothing/eye protection/face protection. P273: Avoid release to the environment. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy

to do - continue rinsing.

P310: Immediately call a POISON CENTER

or doctor/physician.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331: Do NOT induce vomiting.

Supplementary Precautionary P264: Wash thoroughly after handling P302+P352: IF ON SKIN: Wash with soap

and water.

P332+P313: If skin irritation occurs: Get

medical advice/attention.

P362+P364: Take off contaminated clothing

and wash it before reuse. P405: Store locked up.

P501: Dispose of contents/container to hazardous waste or special collection point. EUH066: Repeated exposure may cause

skin dryness or cracking

Hazard Determining Component(s) Hydrocarbons C12-C15 n-alkanes,

> isoalkanes, cyclic, < 2% aromatics Alcohols, C12-C15, branched and linear,

ethoxylated, propoxylated

Alcohols, C11 – C15 secondary ethoxylated

Terpineol

2.3 Other hazards:

(EU)

Statement(s):

Spilled liquid could present a slip hazard.

Supplementary Hazard Information

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

Ingredient Name	CAS No	EC No	REACH Registration Number	% Weight	Classification according to Regulation (EC) No 1272/2008 [CLP]	Additional information
Hydrocarbons C12-C15 n- alkanes, isoalkanes, cyclic, < 2% aromatics	-	920- 107-4	01- 2119453414-43	50 - 70	Asp. Tox. 1: H304	EUH066
Alcohols, C12-C15, branched and linear, ethoxylated, propoxylated	120313- 48-6	-	-	< 15	Eye Dam. 1: H318 Aquatic Chronic 2: H411	None
Alcohols, C11 – C15 secondary ethoxylated	68131- 40-8	614- 295-4	-	< 15	Skin Irrit. 2: H315 Eye Dam. 1 H318	None
Oleic acid monoisopropanolamide	111-05- 7	-	-	< 3	Eye Dam. 1 – H318 Skin. Irrit. 2 – H315	None
Terpineol	8000- 41-7	232- 368-1	01- 2119553062-49	< 2	Skin Irrit. 2: H315 Eye Irrit. 2 H319	None

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished products.

^{*}See Section 16 for hazard statement(s) text in full.

c_{Γ}	\sim T	\sim	NI 4
SE	- I	ıU	N 4

FIRST AID MEASURES

4.1 Description of first aid measures:

General notes: If symptoms persist, seek medical attention.

Show this safety data sheet to the doctor in

attendance.

Following inhalation: Remove to fresh air. Keep at rest. If not

breathing give artificial respiration. Seek medical attention if symptoms occur. Flush with water, use soap if available.

Following skin contact: Flush with water, use soap if available.

Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.

Following eye contact: Flush eyes with large amounts of water for at least 15 minutes. Check for and remove

any contact lenses if easy to do - continue

rinsing. Seek medical attention

immediately.

Following ingestion: Do NOT induce vomiting. If vomiting

occurs, keep head low so that stomach contents don't enter the lungs. Never give anything by mouth to an unconscious person. Seek medical attention

immediately.

Self-protection of the first aider:No action shall be taken involving any

personal risk or without suitable training. If it is suspected that the mixture is still present,

wear appropriate personal protective

equipment.

4.2 Most important symptoms, both acute and delayed:

Risk of serious damage to eyes. May cause lung damage if swallowed. No delayed effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

Eye wash bottle must be readily available when product is in use.

SECTION 5 FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media: Carbon dioxide, foam, dry chemical, water

fog or spray.

Unsuitable extinguishing media: Do not use water jet.

5.2 Special hazards arising from the

substance or mixture:

Hazardous combustion products:

Evacuate immediate area. If possible keep unaffected containers cool with water spray. Smoke, soot and oxides of carbon. Burning

vapour may give off toxic fumes.

5.3 Advice for fire-fighter:

Self contained breathing apparatus and full protective clothing must be worn. Water spray should be used to cool containers.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Suitable protective equipment (see Section 8) should be worn to prevent any

contamination of skin, eyes and personal clothing.

For non-emergency personnel: Remove ignition sources. Avoid breathing

vapours, mist or gas. Ensure adequate ventilation. Vapours are likely to accumulate

in low areas.

For emergency responders: Keep unnecessary people at a safe

distance. Remove ignition sources. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Vapours are likely to

accumulate in low areas.

6.2 Environmental precautions:

Prevent liquid from entering drains, sewers and watercourses. Notify the Environment Agency or water authorities if a major spillage occurs. Prevent product from contaminating soil.

6.3 Methods and material for containment and cleaning up:

Eliminate sources of ignition. Take measures to prevent the build-up of electrostatic charge.

For containment: Contain spilled liquid with sand or earth.

Mop up or absorb onto with non-

combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Place in a container for disposal according

to local/national regulations.

Large spills should be pumped (using an earthed explosion proof pump) into

containers pending disposal.

For cleaning up: Allow residues to evaporate. Do not flush

away residues with water.

Other information:

No other information.

6.4 Reference to other sections:

For Personal Protective Equipment see Section 8. For disposal information see Section 13.

SECTION 7 HANDLING & STORAGE

7.1 Precautions for safer handling:

Protective Measures: Wear suitable protective clothing such as

chemical resistant gloves, apron and goggles/face mask to protect from splashes. Ensure adequate exhaust ventilation when

in use.

Avoid contact with skin and eyes. Do not

breathe product spray or mist.

Keep away from sources of ignition. Take Measures to prevent fire:

measures to prevent the build-up of

electrostatic charge.

Advice on general occupational

hygiene:

Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities:

Technical measures and storage Store in a cool dry area away from heat and conditions:

sources of ignition. Keep containers closed

when not in use.

Store in original container. Packaging materials:

Requirements for storage rooms and

Further information on storage

vessels:

Store locked up.

Recommended storage temperature 10 °C

to 30 °C.

Keep containers out of direct sunlight. Rotate stock and check regularly for

damaged items.

conditions: 7.3 Specific end use(s):

> Recommendations: Use only for Non Destructive Testing (NDT)

> > applications.

Industrial sector specific solutions: See product data sheet for further

information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 **Control parameters:**

Occupational exposure limit values:

Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

Ingredient name	Country	Limit valu	e - 8 hours	Limit value -	short term
	•	ppm	mg /m³	ppm	mg/m³
Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics	Supplier's recommendation	150	1200		
Data obtained from supplier's SDS					

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) – Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	No threshold effect and/or no dose- response information available.
Worker	Inhalation	Short term	Local	No threshold effect and/or no dose- response information available.
Worker	Dermal	Long term	Systemic	No threshold effect and/or no dose- response information available.

Derived No Effect Level (DNEL) - Terpineol

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	5.8 mg/m ³
Worker	Inhalation	Short term	Systemic	5.8 mg/m ³
Worker	Dermal	Long term	Systemic	1.17 mg/kg bw/day
Worker	Dermal	Short term	Systemic	5 mg/kg bw/day

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygenists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Predicted No Effect Concentration (PNEC)

	Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics	Terpineol
Water - Fresh Water	No data available, testing technically not feasible.	62 μg/L
Water - Marine Water	No data available, testing technically not feasible.	6.2 µg/L
Water - Intermittent release	No data available, testing technically not feasible.	No data available.
Sediment - Fresh water	No data available, testing technically not feasible.	0.442 mg/kg sediment dw
Sediment - Marine water	No data available, testing technically not feasible.	0.044 mg/kg sediment dw
Soil	No data available, testing technically not feasible.	0.052 mg/kg soil dw
Sewage Treatment plant	No data available, testing technically not feasible.	2.57 mg/L

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable.

Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

Appropriate engineering controls:

Provide eye wash station.

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded.

Personal protection equipment:

Skin protection - other:

Thermal hazards:

Eye and face protection: Safety glasses with side-shields

conforming to EN166.

Protective gloves conforming to EN374-3. Skin protection - hand:

Use chemical resistant gloves

recommended by glove manufacturer as being suitable for kerosenes if hand

exposure is unavoidable.

Protective gloves made of nitrile.

neoprene or PVC are suitable, although other types may be more suitable in other

circumstances.

For prolonged exposure, recommended gloves with protective index 6, > 480 minutes permeation time according to

EN374.

As the product is a preparation, consult

the glove manufacturer for exact

breakthrough time. Glove manufacturer's directions for use should be observed. Wear impervious clothing. The type of protective equipment must be selected

according to the concentration and amount of dangerous substance at the

specific workplace.

Respiratory protection: If ventilation is insufficient, suitable

> respiratory protection must be provided. Chemical respirator with organic vapour cartridge. Use respiratory equipment with gas filter, type A2. EN 136/140/145/

143/ 149.

For higher level protection use type ABEK-P3 (EU EN 143) respirator cartridges. Use respirators and

components tested and approved under

CEN standards. Not applicable.

Environmental exposure controls: Avoid any release to the environment.

SECTION 9 PHYSICAL & CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

> Appearance: Yellow/ green liquid.

Odour: Mild pine.

Odour threshold: No data available.

:Ha Neutral.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: 230 °C.

Flash point (PMCC): 93 °C (minimum).

Evaporation rate (BuAC = 100): < 0.1.

Flammability (solid, gas) (Limits in air): No data available. Upper/lower flammability or explosive 1.0 - 6.0 % (Vol %).

limits:

Vapour pressure: < 0.5 mm Hg @ 20 °C.

Vapour density (Air = 1): > 1.

0.88 g/cm³. Relative density: Emulsifies. Solubility: Partition coefficient: n-octanol/water: No data available.

Auto-ignition temperature: > 200 °C.

Decomposition temperature:No data available.Viscosity (ASTM D445):7.0 mm²/s @ 38 °C.Explosive properties:No data available.Oxidising properties:No data available.

Note: properties relate to the bulk product only unless otherwise stated.

9.2 Other information:

No other information.

10.1 Reactivity: No data available.

10.2 Chemical stability Stable under normal conditions of use and

applications.

10.3 Possibility of hazardous reactions: No data available.

10.4 Conditions to avoid: Keep away from sources of ignition, hot

surfaces and direct sun light.

10.5 Incompatible materials: Strong oxidising agents.

10.6 Hazardous decomposition materials: None under normal conditions of use.

Smoke, soot and oxides of carbon on

combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: based on data for component materials.

Acute toxicity - oral:Based on the available data, the classification

criteria are not met.

Acute toxicity – dermal: Based on the available data, the classification

criteria are not met.

Acute toxicity – inhalation: Based on the available data, the classification

criteria are not met.

Skin corrosion/irritation: Skin Irrit. 2, H315: Causes skin irritation.

EUH066: Repeated exposure may cause skin

cracking or dryness.

Serious eye damage/irritation: Eye Dam. 1, H318: Causes serious eye

damage.

Respiratory sensitisation: Based on tests of individual components, this

preparation is not sensitising.

Skin sensitisation: Based on tests of individual components, this

preparation is not sensitising.

Germ cell mutagenicity: Based on individual components, this

preparation is not expected to show

mutagenic effects.

Carcinogencity: Based on individual components, this

preparation is not expected to show

carcinogenic effects.

Reproductive toxicity: Based on individual components, this

preparation is not expected to show

repoductive toxicity.

STOT single exposure: Data lacking.

STOT repeated exposure: Data lacking.

Aspiration hazard: Asp. Tox. 1 - H304: May be fatal if swallowed

and enters airways.

Information on likely Routes of Exposure and Potential Health Effects:

Inhalation: May be harmful if inhaled. Causes respiratory

tract irritation.

Ingestion: May be harmful if swallowed. Ingestion may

cause irritation of the mouth, throat and digestive tract. Small amounts of product aspirated into the respiratory system during ingestion or from vomiting may cause bronochopneumonia or pulmonary edema.

Eye contact: Risk of serious damage to eyes.

Skin contact: May be harmful if absorbed through skin.

Causes skin irritation. Repeated exposure

may cause skin cracking or dryness.

Toxicity Test Results: based on data for component materials, where available.

Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

Acute Toxicity – oral	LD50 (rat)	> 5000 mg/kg (OECD 401)
Acute Toxicity – dermal	LD50 (rabbit)	> 5000 mg/kg (OECD 402)
Acute Toxicity – inhalation	LC50 (rat)	4951 mg/l (vapours) 4h (OECD403)

Alcohols, C12-C15, branched and linear, ethoxylated, propoxylated

Acute Toxicity – oral	LD50 (rat)	2,000 – 5,000 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	Not determined
Acute Toxicity – inhalation	LC50 (rat)	Not determined

Alcohols, C11 – C15 secondary ethoxylated

Acute Toxicity – oral	LD50 (rat)	> 3,000 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	> 2,000 mg/kg
Acute Toxicity – inhalation	LC50 (rat)	No data.

Terpineol

Acute Toxicity – oral	LD50 (rat)	4300 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	> 3000 mg/kg
Acute Toxicity – inhalation	LC50 (rat)	No data

Other Information:

No other information

SECTION 12 ECOLOGICAL INFORMATION

Based on data for component materials

12.1 Toxicity:

Hydrocarbons C12-C15 n-alkanes, isoalkanes, cyclic, < 2% aromatics

Alcohols, C12-C15, branched and linear, ethoxylated, propoxylated

Fish	Leuciscus idus	LC50	96h	1 – 10 mg/l (1)
Microorganisms	Activated Sludge	EC10		> 1000 mg/l (DEV-L2)

Alcohols, C11 - C15 secondary ethoxylated

Fish	Pimephales promelas	LC50	96h	3.5 – 4.9 mg/l
Aquatic Invertebrates	Daphnia Magna	EC50	48h	3.1 mg/l.

12.2 Persistence and degradability: Hydrocarbons C12- C15 n-alkanes,

isoalkanes, cyclics, < 2% aromatics:

expected to be biodegradable.

Alcohols, C12-C15, branched and linear,

ethoxylated, propoxylated: moderately biodegradable. Alcohols, C11 – C15 secondary

ethoxylated:

readily biodegradable.

12.3 Bioaccumulative potential: Hydrocarbons C12 - C15 n-alkanes,

isoalkanes, cyclics, < 2% aromatics:

no data available.

Alcohols, C12-C15, branched and linear,

ethoxylated, propoxylated:

Accumulation in organisms is not expected.

Alcohols, C11 - C15 secondary

ethoxylated:

Not expected to be bioaccumulating. **Hydrocarbons C12 - C15 n-alkanes**,

isoalkanes, cyclics, < 2% aromatics:

no data available.

Alcohols, C12-C15, branched and linear,

ethoxylated, propoxylated:

no data available.

Alcohols C11 - C15 secondary

ethoxylated: log Pow = 3.3 - 4.4

Bioconcentration factor (BCF): Alcohols C11 - C15 secondary

ethoxylated: log BCF = 15 - 64

12.4 Mobility in soil: Hydrocarbons C12 - C15 n-alkanes,

isoalkanes, cyclics, < 2% aromatics:

this product is insoluble in water.

Alcohols, C12-C15, branched and linear,

ethoxylated, propoxylated:

The substance will not evaporate into the atmosphere from the water surface. Adsorption to the solid phase is possible.

Alcohols C11 - C15 secondary

ethoxylated:

This product is soluble in water.

12.5 Results of PBT and vPvB assessment: This mixture does not contain any

substances that are assessed to be a PBT or

vPvB.

12.6 Other adverse effects: No data available,

Partition coefficient: n-octanol/water

(log Kow):

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation.

Product/packing disposal: Empty containers may contain residues.

Do NOT remove labels.

Waste codes/waste designations

according to LoW:

None assigned.

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

Waste treatment – relevant information: Dispose of waste and residues in

accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in

accordance with national legislation

Do not empty down the drain.

Sewage disposal – relevant

information:

Not applicable.

Other disposal recommendations: Use a licensed waste contractor.

SECTION 14 TRANSPORT INFORMATION

14.1	UN number:	ADR/RID:	-
		IMDG:	-
		IATA:	-
14.2	UN proper shipping name:	ADR/RID:	Not dangerous goods.
		IMDG:	Not dangerous goods.
		IATA:	Not dangerous goods.
14.3	Transport hazard class(es):	ADR/RID:	-
	. ,	IMDG:	-
		IATA:	-
14.4	Packing group:	ADR/RID:	-
		IMDG:	-
		IATA:	-
14.5	Environmental hazards:	ADR/RID:	-
		IMDG:	-
		IATA:	-
14.6	Special precautions for user:		
	Not applicable.		
14.7	Transport in bulk according to Annex II of	Marpol 73/78 ar	nd the IBC code:

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations:

This data sheet complies with the requirements of Regulation (EC) No. 1272/2008 on the classification, labelling and packaging of substances and mixtures.

Safety data sheet as required by EU Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.

Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.

Not applicable this product is not an aerosol.

National regulations (Germany):

Wassergefahrdungklasse (water WGK 2 - Hazard to waters.

hazard class):

Technische Anleitung Luft (TA-Luft): Class 5.2.5 Organic substances, except

dusts.

15.2 Chemical safety assessment:

No chemical safety assessment has been carried out for this mixture by the supplier.

SECTION 16 OTHER INFORMATION

(i) Indication of changes:

Version 17.1 updated in Section 1.4.

Vertical lines on the left hand side indicate an amendment from the previous version.

(ii) Abbreviations and acronyms:

ADR European Agreement concerning the International Carriage of Dangerous Goods

by Road (Accord européen relatif au transport international des marchandises

Dangereuses par Route)

CAS No. Chemical Abstracts Service number
CEN European Committee for Standardisation

CLP Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008

ECHA European Chemicals Agency EC50 Half Maximal Effective Concentration

EC number EINECS and ELINCS number

EINECS European Inventory of Existing Commercial Substances

ELINCS European List of notified Chemical Substances

GHS Globally Harmonized System

IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC50 Lethal Concentration to 50% of a test population

LD50 Lethal Dose to 50% of a test population

MPI Magnetic Particle Inspection
NDT Non-Destructive Testing
OEL Occupational Exposure Limit

PBT Persistent, Bioaccumulative and Toxic Substance

PMCC Pensky-Martens closed cup method PPE Personal Protection Equipment

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

EC (No) 1907/2006

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

(Reglement International concernant le transport des marchandises Dangereuses

par chemin de fer) Safety Data Sheet

SDS Safety Data Sheet
STOT RE Specific Target Organ Toxicity, Repeat Exposure
STOT SE Specific Target Organ Toxicity, Single Exposure

TA-Luft Technical Instructions on Air Quality Control(Technische Anleitung zur

Reinhaltung der Luft)

vPvB Very Persistent and Very Bioaccumulative

WEL Workplace Exposure Limit

WGK German Water Hazard Class(Wassergefährdungsklasse)

(iii) Key literature and sources of data:

• Supplier's safety data sheets for components listed in Section 3.

- European Chemicals Agency, http://echa.europa.eu/
- GESTIS International Limit Values Database, http://limitvalue.ifa.dguv.de/Webform_gw.aspx
- Occupational Exposure Limits EH40/2005.
- Regulation (EU) No. 2015/830.
- Control of Substances Hazardous to Health Regulations 2002.
- Hazardous waste regulations 2005.
- Health & Safety at Work Act 1974.
- Regulation (EC) No. 1907/2006 (REACH).
- Regulation (EC) No. 1272/2008 (CLP).

(iv) Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):

Classification according to Regulation (EC) No 1272/2008	Classification procedure		
Eye Dam. 1 H318	Calculation – non additive approach		
Asp Tox 1 H304	Calculation		
Skin Irrit. 2 H315	Calculation		
Aquatic Chronic 3 H412	Calculation		

(v) Hazard statements (number and full text):

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard Class Category Code (number and full text):

Aquatic Chronic 2: Hazardous to the aquatic environment Aquatic Chronic 3: Hazardous to the aquatic environment

Asp. Tox. 1: Aspiration hazard

Eye Dam. 1: Serious eye damage/eye irritation

Eye Irrit. 2: Serious eye damage/eye irritation

Skin Irrit. 2: Skin corrosion/irritation

Relevant precautionary statements (number and full text):

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release to the environment.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331: Do NOT induce vomiting.

P264: Wash thoroughly after handling

P302+P352: IF ON SKIN: Wash with soap and water.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P405: Store locked up.

P501: Dispose of contents/container to hazardous waste or special collection point.

(vi) Training advice:

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment. Provide adequate information, instruction and training to operators.

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-to-date and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

Revision Revision This SDS is valid from the Revision Date. If you require a SDS for the summary: Comments product manufactured before the revision date please contact us at

datasheets@magnaflux.co.uk.

Revision Date 01.01.2017

Version 17.1